

16CH Real-Time

SA-16400NE



■ Front Panel



■ Rear Panel



SPECIFICATIONS

MODEL		SA-16400NE
System	Compression Format	H.264
	OS	Embedded Linux
Video	Input	16CH, BNC(1.0Vp-p, 75Ω)
	Standard Output	1*BNC Mainout 1*Spot 1*VGA:1280x1024,800x600,1024x768
Audio	Audio Input	4CH
	Audio Output	1CH
	Two way audio	YES
Recording	Real Time Recording	16CH CIF real time
	D1(4CIF)	120(NTSC)/100PAL)fps
	CIF	480(NTSC)/400PAL)fps
	Recording Mode	Schedule, Manual, Motion, Sensor
Playback	Playback Channel	16CH
	Search Mode	Time ,Event,File Mangement,Image(snapshot)
Backup	USB Disk	1 USB 2.0 port
	DVD Burner	Optional
	Backup Format	DAT or AVI
Remote Application	Dual Stream	Master stream :1~25/30fps@4CIF/CIF Network stream:1~6/7fps@CIF
	Browser	IE(Windows XP /2000/vista/9),Safari(Mac OS)
	Master Stream in Network	-
	CMS	YES
	3G	Super Cam/pro/HD for iPad/iPad2/iPhone/Blackberry/Android/Symbian/Windows mobile
	User Access	-
Alarm	Alarm Input	16CH
	Alarm Output	1CH
Storage	HDD	2SATA-4TB
PTZ	PTZ	1*RS485
	PTZ Protocol	PELCO-P, PELCO-D, LILIN, MINKING, NEON, STAR, VIDO, DSCP, VISCA, SAMSUNG, RM110, HY
	PTZ Control	pan, tilt, zoom, preset, cruise, trace
Network	Ethernet	10/100 Mbps Ethernet (RJ-45)
	Protocol	TCP/IP, DHCP, DDNS, NTP, SMTP
Others	Dimension	W430xD420xH90mm
	IR Controller	x1, with IR extension option
	Power Supply	DC 12V/4A
	Operating Temperature	0℃~50℃